



**NXT Power 1500 VA 120 VAC Wall Mount Bypass
switch REV A.**



Rev A: Released

June 3, 2025

1 Basic

This specification outlines (1) wall mount bypass switch for a 120 VAC 1500VA rated UPS

2 General product information

1500VA wall mount hard wired bypass switch

VA Rating	Model Number	Input Voltage	Output Voltage	Frequency
1500	Power Hub 1500	120	120	50/60 Hz

3 Electrical Characteristics

- a) 120 VAC rated for 12 amps
- b) Bypass switch break before make.
- c) Wall mount
- d) Hardwired input and output
- e) The enclosure temperature must not exceed 40 degrees C on any surface
- f) convection cooled
- g) UPS available LED Green
- h) Bypass available LED Yellow
- i) Compatible with NXT Power NPTU1500-OR-N ups

4 Enclosure

- a) Painted steel black with white silk screen
- b) Unit weight 4.5lbs

5 Input and output connections

- a) Hardwired and plug and receptacle

b) Environment usage and transport.

- a) Operating Temperature 0 to 40 degrees C
- b) Operating Humidity 5% to 90%
- c) Maximum operating altitude 2,000 meters
- d) Storage temperature -18 to 65 degrees C
- e) Storage Humidity 5% to 95%
- f) Maximum transportation altitude 15,000 meters
- g) All units packaging meets ISTA Series 1A

c) Safety and compliance

- a) Listed to UL1778 as UPS accessory (cULus)

d) Drawings (inches)

