



FOR MEDIUM OR LARGE ELECTRONIC SYSTEMS

> INTEGRITY THREE-PHASE POWER CONDITIONER

Designed for use with large system power requirements, the Integrity 3-Phase allows you to control the electrical environment feeding your sensitive electronic systems, increasing uptime, reducing service calls, and increasing productivity.

EXPERIENCE SUPERIOR POWER PROTECTION

Integrity 3-Phase Power Conditioners incorporate a low impedance transformer, as well as a surge diverter and a power line filter to eliminate noise, spikes, and transients from effecting the operation for your electronic systems.

Designed for WORLDWIDE applications.

SUITABLE FOR USE WITH:

- > Semiconductor Manufacturing
- > Digital Printing
- > Computer Controlled Equipment
- > Lab Automation Systems



SUPERIOR POWER PROTECTION BENEFITS & FEATURES

- Protect your electronic systems and ensure uptime all day, every day.
- Peace of mind knowing equipment is protected from problems due to common-mode voltage, spikes, transients, and more.
- Includes emergency machine off (EMO) and lockout/tagout breaker.
- Let through voltage is less than 10 volts normal mode and less than 0.5 volts. Neutral-to-ground when tested to ANSI/IEEE C62.41, Category A&B.
- Power options from 10 kVA to 75 kVA 3-Phase.
- Provides clean power at 208, 240, or 480 delta input and 208/120, 400/230 or 480/277 wye output.
- UL listed
- Includes NXT Power 5 Year Warranty

NXTPOWER

7051 W Wilson Ave, Norridge, IL 60706

NXTPower.com | Contact@NXTPower.com

(877) NXT-POWR or (877) 698-7697



INTEGRITY THREE-PHASE POWER CONDITIONER

> PRODUCT SPECIFICATIONS

INTERNATIONAL

MODEL #	INPUT VOLTAGE AC~	OUTPUT VOLTAGE AC~	MAXIMUM POWER (KVA)	FREQUENCY (HZ)
NPT10.0-H-i	400	208/120, 400/230 or 480/277	10 kVA	50/60
NPT15.0-H-i	400	208/120, 400/230 or 480/277	15 kVA	50/60
NPT20.0-H-i	400	208/120, 400/230 or 480/277	20 kVA	50/60
NPT30.0-H-i	400	208/120, 400/230 or 480/277	30 kVA	50/60
NPT36.0-H-i	400	208/120, 400/230 or 480/277	36 kVA	50/60
NPT40.0-H-i	400	208/120, 400/230 or 480/277	40 kVA	50/60
NPT55.0-H-i	400	208/120, 400/230 or 480/277	55 kVA	50/60
NPT65.0-H-i	400	208/120, 400/230 or 480/277	65 kVA	50/60
NPT75.0-H-i	400	208/120, 400/230 or 480/277	75 kVA	50/60

ADDITIONAL PRODUCT INFORMATION

- Measurements of model(s) NPT10.0-H-N to NPT30.0-H-N are 82.8cm(H) x 50.8cm(W) x 83cm(D)
- Measurements of model(s) NPT36.0-H-N to NPT75.0-H-N are 115cm(H) x 50.8cm(W) x 109.2cm(D)

**WE ARE DEDICATED TO PRODUCING THE
BEST POWER QUALITY SOLUTIONS AND
PRODUCTS FOR YOUR BUSINESS.**

We manufacture power quality solutions using proven technology and the latest industry knowledge to deliver the cleanest, most reliable power available to businesses in a diverse range of markets and industries.

NXTPOWER

7051 W Wilson Ave, Norridge, IL 60706

NXTPower.com | Contact@NXTPower.com

(877) NXT-POWR or (877) 698-7697