

NXTPOWER

FOR MEDIUM OR LARGE ELECTRONIC SYSTEMS

› INTEGRITY THREE-PHASE POWER CONDITIONER

Designed for use with large system power requirements, the Integrity 3-Phase allows you to control the electrical environment feeding your sensitive electronic systems, increasing uptime, reducing service calls, and increasing productivity.

EXPERIENCE SUPERIOR POWER PROTECTION

Integrity 3-Phase Power Conditioners incorporate a low impedance transformer, as well as a surge diverter and a power line filter to eliminate noise, spikes, and transients from effecting the operation for your electronic systems.

Designed for WORLDWIDE applications.



SUITABLE FOR USE WITH:

- › Semiconductor Manufacturing
- › Digital Printing
- › Computer Controlled Equipment
- › Lab Automation Systems

SUPERIOR POWER PROTECTION BENEFITS & FEATURES

- Protect your electronic systems and ensure uptime all day, every day.
- Peace of mind knowing equipment is protected from problems due to common-mode voltage, spikes, transients, and more.
- Includes emergency machine off (EMO) and lockout/tagout breaker.
- Let through voltage is less than 10 volts normal mode and less than 0.5 volts. Neutral-to-ground when tested to ANSI/IEEE C62.41, Category A&B.
- Power options from 10 kVA to 75 kVA 3-Phase.
- Provides clean power at 208, 240, or 480 delta input and 208/120, 400/230 or 480/277 wye output.
- UL listed
- Includes NXT Power 5 Year Warranty

NXTPOWER

7051 W Wilson Ave, Norridge, IL 60706

NXTPower.com | Contact@NXTPower.com

(877) NXT-POWR or (877) 698-7697



INTEGRITY THREE-PHASE POWER CONDITIONER

▶ PRODUCT SPECIFICATIONS

WORLDWIDE

MODEL #	INPUT VOLTAGE AC [~]	OUTPUT VOLTAGE AC [~]	MAXIMUM POWER (KVA)	FREQUENCY (HZ)
NPT10.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	10 kVA	50/60
NPT15.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	15 kVA	50/60
NPT20.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	20 kVA	50/60
NPT30.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	30 kVA	50/60
NPT36.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	36 kVA	50/60
NPT40.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	40 kVA	50/60
NPT45.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	45 kVA	50/60
NPT55.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	55 kVA	50/60
NPT65.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	65 kVA	50/60
NPT75.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	75 kVA	50/60
NPT85.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	85 kVA	50/60
NPT100.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	100 kVA	50/60
NPT125.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	125 kVA	50/60
NPT150.0-H-N	208, 240 or 480	208/120, 400/230 or 480/277	150 kVA	50/60

ADDITIONAL PRODUCT INFORMATION

- Measurements of model(s) NPT10.0-H-N to NPT30.0-H-N are 29.3in(H) x 20in(L) x 32.70in(D)
- Measurements of model(s) NPT36.0-H-N to NPT75.0-H-N are 42in(H) x 20in(L) x 41.41in(D)
- Measurements of model(s) NPT85.0-H-N to NPT150.0-H-N are 60.6in(H) x 28in(L) x 46.10in(D)

NXTPOWER

7051 W Wilson Ave, Norridge, IL 60706

NXTPower.com | Contact@NXTPower.com

(877) NXT-POWR or (877) 698-7697

